



6×7 SK11J01

構成 6×(1+6)

用途 リフト支曳索用、索道の主索・曳索用、立坑・斜坑巻上用、立坑掘削ガイド用、底曳用、ステアー用（含船舶用）

規格

ロープ径 mm	上層素線径 mm	断面積 mm ²	破断力						(参考) 単位質量 kg/m
			めっき		裸				
			G 種		A 種		T 種		
			kN	(参考) tf	kN	(参考) tf	kN	(参考) tf	
6	0.67	14.8	19.0	1.93	21.4	2.18	24.7	2.51	0.134
8	0.88	26.3	33.8	3.44	38.1	3.88	43.9	4.47	0.237
9	1.00	33.3	42.8	4.36	48.2	4.91	55.6	5.66	0.300
10	1.10	41.1	52.8	5.38	59.5	6.06	68.6	6.99	0.371
12	1.33	59.1	76.0	7.74	85.6	8.72	98.8	10.0	0.534
14	1.56	80.5	103	10.5	117	11.9	134	13.6	0.727
16	1.78	105	135	13.7	152	15.4	176	17.9	0.950
18	2.00	133	171	17.4	193	19.6	222	22.6	1.20
20	2.20	164	211	21.5	238	24.2	274	27.9	1.48
22	2.44	199	256	26.1	288	29.3	332	33.8	1.80
24	2.66	237	304	30.9	343	34.9	395	40.2	2.14
26	2.86	278	357	36.4	402	40.9	464	47.3	2.51
28	3.12	322	414	42.2	466	47.5	538	54.8	2.91
30	3.30	370	475	48.4	535	54.5	—	—	3.34
32	3.55	420	541	55.1	609	62.1	—	—	3.80