



6×37 SK11J04

構成 6×(1+6+12+18)

用途 クレーン等荷役用、玉掛用、係留索・カーゴ等船舶用、リフト・索道の緊張索用、  
その他諸機械用

規格

ロープ径 mm	上層素線径 mm	断面積 mm <sup>2</sup>	破断力				(参考) 単位質量 kg/m
			めっき		裸		
			G 種		A 種		
			kN	(参考) tf	kN	(参考) tf	
6	0.29	14.1	17.8	1.81	19.1	1.94	0.129
8	0.38	25.2	31.6	3.22	34.0	3.46	0.230
9	0.43	31.8	40.0	4.07	43.0	4.38	0.291
10	0.48	39.3	49.4	5.03	53.1	5.41	0.359
12	0.57	56.6	71.1	7.25	76.5	7.80	0.517
14	0.67	77.0	96.7	9.86	104	10.6	0.704
16	0.76	101	126	12.8	136	13.8	0.920
18	0.86	127	160	16.3	172	17.5	1.16
20	0.95	157	197	20.0	212	21.6	1.44
22	1.05	190	239	24.3	257	26.2	1.74
24	1.14	226	284	28.9	306	31.2	2.07
26	1.22	266	334	34.0	359	36.6	2.43
28	1.33	308	387	39.4	416	42.4	2.82
30	1.41	354	444	45.2	478	48.7	3.23
32	1.52	402	505	51.4	544	55.4	3.68
36	1.70	509	640	65.2	688	70.1	4.66
40	1.88	629	790	80.5	850	86.6	5.75
44	2.08	761	956	97.4	1,030	105	6.96
48	2.27	905	1,140	116	1,220	124	8.28
52	2.48	1,060	1,330	135	1,440	146	9.72
56	2.66	1,230	1,550	158	1,670	170	11.3
60	2.86	1,410	1,780	181	1,910	194	12.9